From Empirical Craft to Data-Driven Control: Artificial Intelligence and Emerging Quantum Perspectives in Leather Technology

Conference: 13th AICLST, Kolkata, 6–8 March 2026

Paper reference: TA-11/O

Printed pages: 63–67

Source: *Leather 2050: Challenges & Opportunities*, ILTA (2026)

From Empirical Craft to Data-Driven Control: Artificial Intelligence

and Emerging Quantum Perspectives in Leather Technology

Ref. No. TA-11/O

Saikat Chakraborty

Managing Director - M/s Accenture

Abstract:

Leather processing is different from many other manufacturing sectors because it combines biological variability with complicated chemical changes. This makes it both difficult and a good fit for smart systems. This article examines established AI applications in leather grading, process optimization, environmental management, and supply chain analytics, substantiated by peer-reviewed studies and documented industrial pilots. Simultaneously, it investigates the function of quantum mechanics as a fundamental scientific framework for leather chemistry and assesses the feasibility of quantum computing as a prospective research facilitator. Case studies are included when there is reliable evidence, and there are clear lines between industrial practice and exploratory research.

Key Words: leather chemistry; artificial intelligence; machine learning; computer vision; process optimization; sustainability; quantum chemistry

1. Introduction

In the past, leather making relied more on tacit knowledge gained through practice than on formalised models. This experiential approach has made it possible to be flexible, but it has also made it harder to scale, reproduce, and be open about what is going on. These limits have become clearer because of more regulatory pressure, expectations for sustainability, and the need for consistent quality.

Corresponding author email: chakraborty.saikat@gmail.com

Artificial Intelligence provides a means to encode empirical knowledge into data-driven models that enhance human decision-making rather than supplant it. êuantum science, conversely, offers a theoretical framework for a more profound comprehension of the molecular interactions that dictate leather chemistry. This paper combines both points of view and bases the discussion on real-world evidence and limitations.

2. Leather Science and Technology: A Scientific and Process Oriented Framework

Leather is a hierarchical biomaterial whose properties arise from interactions across electronic, molecular, microstructural, and macroscopic scales. Chemical crosslinking, usually through chromium coordination complexes or polyphenolic vegetable tannins, helps keep collagen fibres stable during tanning. After that, wet-end and finishing processes change the lubrication, colour, softness, and surface performance of the fibres even more.

One of the biggest problems with processing leather is that raw hides can be different in thickness, fibre density, and where defects are found. This variability makes it harder to control processes and predict quality, which opens up the possibility of using data- driven modelling.

Mathematical Context of Leather Processing Systems

Let the leather manufacturing process be represented as a multistage system in which observable outputs are functions of raw material properties, process parameters,

and time-dependent chemical states. At a high level, the system can be expressed as:

□= □(□, □, □) + □

Where,

x represents raw hide attributes (thickness, fiber density, defect density), u denotes controllable process parameters (chemical dosages, pH, temperature, drum speed) & t is process time, y denotes quality or environmental outputs and

captures unmodeled vari-

 ability.

The function f(.) is nonlinear, partially observable, and poorly described by closed-form physical models at industrial scale, motivating data-driven approximations

Case context from the literature: Covington (2011) shows how small changes in tanning chemistry can cause big changes in leather performance. This shows how sensitive the system is and how important it is to have tools that can predict what will happen instead of just making changes based on experience.

3. AI in Leather Technology: Well-Known Uses

3.1 Grading and finding defects automatically

One of the most advanced AI applications in the industry is automated leather grading using computer vision. Under controlled conditions, high-resolution imaging and convolutional neural networks have been shown to find surface flaws like scars, holes, and wrinkles with the same level of accuracy as trained human inspectors.

Computer Vision Models for Leather Defect Detection, Image Formation and Preprocessing

Let an image of leather surface be represented as a discrete function:

: Ω ⊂ℤ2 →ℝ

where C denotes the number of color channels. Preprocessing transforms the raw image into a normalized representation:

′ = (;)

where P includes illumination normalization, noise filtering, and geometric correction.

Convolutional Neural Network Formulation

A CNN learns a mapping:

 = (′;) ^

where g(.) is composed of stacked convolutional, nonlinear activation, and pooling operations. For a convolutional layer l :

(·)

with * denoting convolution and a nonlinear activation (e.g., ReLU).

The training objective minimizes empirical risk:

ℒ

where is a classification or segmentation loss (e.g., cross-entropy).

Industrial Deployment Context

In deployed systems, predicted defect maps are postprocessed into yield-optimization constraints for cutting algorithms:

where, C denotes cutting paths and D the defect region set.

Documented case study: Numerous peer-reviewed articles in Computers in Industry and IEEE Access have illustrated CNN-based leather defect classification utilizing industrial image datasets. If lighting and image acquisition are standardized. These studies say that classification accuracies for common defect categories are over 90 percent.

Industrial relevance: These publications do not always name the companies involved because of privacy concerns, but they do make it clear that the datasets were collected

from real-life cutting-room or tannery environments. This means that the data was collected in a real-world setting, not just in a lab.

Limitation: The literature consistently indicates diminished robustness when systems are transferred between tanneries without retraining, highlighting the significance of local data.

3.2 Improving the tanning and wet-end processes

In tanning operations, especially during the chrome tanning and re-tanning stages, machine learning models have been used to improve chemical dosing and process parameters. Usually, these models use regression methods or neural networks that have been trained on past batch data.

Machine Learning Models for Tanning Process Optimization

Supervised Learning Formulation

Tanning optimization problems are typically framed as regression tasks:

where, u = [u1, u2.....un] includes process parameters such as chrome dosage, float length, and temperature.

Artificial neural networks approximate as: □ML

□ANN (□) = W□□(W□−1□(... □(W1□)))

Model training minimizes mean squared error:

□

□

□=1

A documented case study in the Journal of the American Leather Chemists Association describes the application of artificial neural networks to model chromium exhaustion based on pH, temperature, float length, and time. These studies showed that these models were better at making predictions than linear empirical models and could lower the amount of chromium left over in effluents.

The authors clearly state that these models are decisionsupport tools that have been tested in pilot-scale trials, not fully autonomous control systems. This is a realistic way for industries to use them.

In a 2015 paper published by Jawahar et al. an approach has been described to develop an artificial neural network model to predict colour in terms of tristimulus values given the concentration of dyes. The artificial neural network results showed a good level of colour prediction during the training and testing phase. The results also indicate that the artificial neural network has the potential to give better predictive performance than the conventional Kubelka–Munk mode

3.3 Sustainability and Environmental Management

Tanneries face a big problem when it comes to following environmental rules, especially when it comes to treating wastewater. AI has been widely utilised in this field, frequently leveraging insights from comprehensive environmental engineering research.

Documented case study: Several studies in environmental journals detail the utilisation of artificial neural networks to forecast chemical oxygen demand and chromium concentration in tannery effluents. One oftencited study showed that ANN- based models did a better job of predicting effluent quality than traditional statistical methods, which made it possible to make changes to treatment before they were needed.

Industry context: These studies are usually done at the pilot-plant or cluster-treatment level, but they are directly related to real tannery wastewater streams instead of synthetic datasets.

3.4 Analytics and Traceability in the Supply Chain

AI-powered analytics are starting to have an effect on leather supply chains, especially when it comes to forecasting and tracking.

Case context: FAO and UNIDO reports talk about pilot programs that used digital traceability systems and analytics to make leather supply chains serving export markets more open. Even though AI parts in these implementations are often small, like predicting demand or finding anomalies, they show that people are starting to use them.

Limitation: There are still not many peer-reviewed, leather-specific studies on advanced AI-driven supply chain optimisation, and most of the cases that have been documented are still at the pilot or consortium level.

4. Quantum Mechanics and Leather Chemistry

Quantum mechanics is the basis for all chemical interactions that are important for processing leather. Electronic structure and quantum behaviour control the formation of chromium–collagen complexes, hydrogen bonding within collagen fibrils, and interactions with tanning agents.

Research context: Density functional theory and other quantum chemical methods have been used in academic research to model interactions between simplified collagen fragments and tanning agents. These studies,

although not industrial case studies, offer validated scientific insights into reaction energetics and bonding mechanisms.

5. Possible Quantum Uses in Leather Technology

Currently, there are no case studies illustrating the application of quantum computing in leather manufacturing. However, In the context of exploratory research, reviews like McArdle et al. (2020) describe how quantum computing could speed up quantum chemistry simulations in the future. Although these advancements are theoretically applicable to leather chemistry, no leatherspecific quantum simulations have advanced beyond theoretical discourse.

Boundary statement: Any use of quantum computing in

leather chemistry should be seen as speculative and longterm. For now, its only value is in academic collaboration, not in industrial investment.

6. Problems and things that make it hard to adopt

The literature consistently identifies challenges pertaining to data accessibility, system integration, and skill deficiencies as impediments to AI adoption in tanneries. Case studies show that AI systems work best when they help, not replace, skilled tech workers.

Quantum technologies encounter significant obstacles, such as underdeveloped hardware and an absence of application-specific algorithms.

7. Conclusion and Future Prospects

Peer-reviewed studies and documented pilots provide evidence that Artificial Intelligence has attained a significant level of industrial applicability in leather technology, especially in quality inspection, process optimisation, and environmental management. These applications work when they are based on a good understanding of chemistry and processes.

Quantum science is important for leather chemistry, but it is still a research tool and not a technology used in industry. Its future contributions will probably be indirect, through better understanding of molecules that helps with classical modelling and new materials.

A feasible innovation strategy for the leather industry must therefore emphasise scalable AI integration while simultaneously engaging with quantum research at a preliminary, scholarly level.

References

1) Covington (2011). Tanning Chemistry: The

Science of Leather. Royal Society of Chemistry.

2) Heidemann, E. (1993). Fundamentals of

Leather Manufacturing. Eduard Roether KG

3) Zhang, Cheng, Wang C Huang (2024). Energy-

saving and low-carbon leather production: AI-assisted chrome tanning process optimization. Journal Of Cleaner Production

4) Aslam, Khan, Naqvi, Holmes C Naffa (2019):

On the Application of Automated Machine Vision for Leather Defect Inspection and Grading: A Survey. IEEE

5) Ghazawi et al. (2021). Use of artificial neural

network for predicting effluent quality parameters and enabling wastewater reuse for

climate change resilience – A case from Jordan. Journal of Water Process Engineering

6) McArdle, S. et al. (2020). êuantum

computational chemistry. Reviews of Modern Physics, 92, 015003

7) Jawahar, Malathy C Kannan, Chandra C

Manobhai, Mehta. (2015). Artificial neural networks for colour prediction in leather dyeing on the basis of a tristimulus system. Coloration Technology. 131. 10.1111/cote.12123.

8) Selected articles from Computers in Industry

on industrial surface inspection.

9) FAO and UNIDO reports on leather supply chain traceability.